

Non-Woven Flap Discs



Non-Woven Flap Discs are used for the deburring, polishing and blending of all kinds of surfaces and welds. Particularly popular for stainless steel applications. Offering a range of satin or mirror finishes.

Santek flap Discs are made in a range of different constructions, offering a choice in flexibility, aggression, hardness and cutting action.

Safety



Non-Woven Flap Discs perform best between 15-50m/s, this giving the optimum balance between stock removal, surface finish, cutting temperature and life.

NB! Excess speed is dangerous and may result in the disc disintegration, flaps pulling out, grain shedding and overheating.

NEVER USE FLAP DISCS AT SPEEDS IN EXCESS OF 60m/s.

Do not use wet or in any coolant or oil.

Use in accordance to ANSI B7.1.

Standard Sizes Surface Conditioning *

Diameter	V-Fine	Fine	Med	Coarse
115mm	•	•	•	•
178mm	•	•	•	•

Sizes Non-Woven Interleaved Δ

Diameter	V-Fine P240	Fine P180	Med P120	Coarse P80
115mm	•	•	•	•
178mm	•	•	•	•

Standard Sizes Quick-Strip Δ

Diameter	V-Fine	Fine	Med	Coarse
115mm	•	•	•	•
178mm	•	•	•	•



Standard Sizes Non-Woven Fleece Δ

Diameter	V-Fine	Fine	Med	Coarse
115mm	•	•	•	•
178mm	•	•	•	•



Standard

Standard



Sizes Quick-Strip *

Diameter	Coarse P80
115mm	•
178mm	•



Unitized Discs are available with both Alox and SiC. Available in a Soft, Med and Hard compound.