

Quick-Loc Non-woven Discs



Non-Woven Quick-Loc Discs are used for, light deburring, polishing, decorative finishing and blending of all kinds of surfaces in both general and tight spaces.

Available with an option of a plastic male or a female metal, thread button.



Safety



Quick-Loc Discs perform best between 10-20m/s, this giving the optimum balance between stock removal, surface finish, cutting temperature and wheel life.

NB! Excess speed is dangerous and may result in product disintegration, grain shedding and overheating.

NEVER USE QUICK-LOC DISCS AT SPEEDS IN EXCESS OF 25m/s.

Do not use wet or in any coolant or oil.

Use in accordance to ANSI B7.1.

Diameter	Recommended Speed rpm	Maximum Speed rpm
30mm	7000	10000
50mm	5500	7500
75mm	3800	5000

Disc Holder



Standard Sizes Surface Conditioning

Diameter	V-Fine	Fine	Med	Coarse
30mm	●	●	●	●
50mm	●	●	●	●
75mm	●	●	●	●



Standard Sizes Quick-Strip Disc

Diameter	Coarse
50mm	●
75mm	●



Unitized Discs are available with both Alox and SiC grain.

Available in a Soft, Med and Hard compound.



Standard Sizes Unitized Disc

Diameter	V-Fine	Fine	Med	Coarse
50mm	●	●	●	●
75mm	●	●	●	●